



Spiral ducts type SD

Circular spiral ducts with standard length of 3 m, made out of galvanized steel sheet of "Sendzimir" quality, with flat folded joint to obtain rigidity and airtightness. The airtightness class is up to class C according EN 12237. The airtightness class is also determined by the mounting on the construction site.

Transport

- **Losse 3 meter buizen worden niet verstuurd en kunnen alleen afgehaald worden.**

Buizen L.3000mm >Ø315 worden in buizenbok verstuurd

Buizen L.3000mm Ø315 en aantal >4 stuks worden in buizenbok verstuurd

Buizen L.3000mm Ø250 of kleiner, maar aantal >6 stuks worden in buizenbok verstuurd

Alle diameters kleiner of gelijk aan Ø315 en/of aantallen die lager zijn dan bovenstaande, worden aangepast naar 2 meter lengtes en voorzien van losse koppelstukken.

Application

- Ducts type **SD** are used for air supply and exhaust in ventilation and air conditioning systems

Material

- Galvanized steel

Thickness

- Dia 080 - 150 mm: 0,4 mm
- Dia 160 - 250 mm: 0,5 mm
- Dia 280 - 500 mm: 0,6 mm
- Dia 560 - 800 mm: 0,8 mm
- Dia 900 - 1250 mm: 1,0 mm

Accessories

- Suspension brackets, type **OBMC** (with rubber sealing)
- Connection pieces with rubber sealing, type **MGM**
- Aluminium tape, type **ALUTAPE**, **ALUTAPE 40S** or cold shrinking tape, type **PSB**, type **ASP**

Spiral duct and fittings

Order example

■ SD, 250 + OBMC

Explanation:

SD = Duct type L= 3m

250 = Diameter of the duct

Accessories:

OBMC = Clamp type

Transportation costs voor ducts > Ø630 and/or > length 3M will be charged to the customer (see our General Sales Conditions).